









GENERAL SPECIFICATIONS

| 9 V» | 11 V | 13 V |
|-------------|---|--|
| 9 yd³ | 11 yd³ | 13 yd³ |
| 82″ | 96" | 96" |
| 71″ | 72" | 72" |
| 191.5" | 195″ | 211″ |
| 9,290 lbs | 9,650 lbs | 10,012 lbs |
| 2 yd³ | 2.7 yd³ | 2.7 yd³ |
| 60" | 80" | 80″ |
| Frame | | Frame |
| 26-30 secs. | 22-24 secs. | 22-24 secs. |
| | 9 yd³ 82″ 71″ 191.5″ 9,290 lbs 2 yd³ 60″ Frame | 9 yd³ 11 yd³ 82" 96" 71" 72" 191.5" 195" 9,290 lbs 9,650 lbs 2 yd³ 2.7 yd³ 60" 80" Frame Frame |

MINIMUM CHASSIS SPECIFICATIONS (STANDARD)

| Model | 9 V» | 11 V | 13 V |
|----------------|------------|------------|------------|
| **Minimum GVWR | 23,000 lbs | 26,000 lbs | 29,000 lbs |

HYDRAULIC CYLINDER SPECIFICATIONS (STANDARD)

| Model | 9 V» | 11 V | 13 V | |
|------------------------|--------------|--------------|--------------|--|
| Slide Cylinders (2) | 4" | 4" | 4" | |
| Sweep Cylinders (2) | | 5" | 5" | |
| Tailgate Cylinders (2) | 3.5" | 3.5" | 3.5" | |
| Ejection Cylinder | 3-Stage 5.5" | 3-Stage 5.5" | 4-Stage 6.5" | |

BODY CONSTRUCTION

| Roof & Sides | 10 gauge | 80K GR |
|--------------------------|----------|---------|
| Floor (center) | 1/4" | 50K GR |
| Floor (sides) | 10 gauge | 80K GR |
| Ejection Panel | 10 gauge | 50K GR |
| Sweep Panel | 1/4" | 80K GR |
| Tailgate (upper & lower) | 10 gauge | 50K GR |
| Hopper Floor | 1/4" | 50K GR |
| Hopper Floor (back) | 1/4" | 100K GR |
| Side Panel | 7 gauge | 50K GR |

HYDRAULIC SYSTEMS

| Oil Reservoir | 45 gal |
|------------------------|--------------|
| Oil Flow w/std. pump | 25 gpm |
| Min. Accept. Oil Flow | 20 gpm |
| Operating Pressure | 2,350 psi |
| Engine RPM for STD gpm | 1,350-1,550 |
| Hydraulic Hoses | 4-to-1 burst |
| Return Filter | 10 micron |

STANDARD EQUIPMENT

- Semi automatic cycling
- Accelerator kit
- Auto-lock tailgate
- Back up alarm
- LED safety lights & reflectors
- Upper rear lights
- Sight gauge on oil tank
- Chrome cylinder rods
- Side access door
- Driver alert buzzer
- Tailgate ajar indicator

- Color rear vision camera system

OPTIONAL EQUIPMENT

- Special lighting
- PTO
- Container lifts (commercial & residential)
- Pack at low idle
- Hopper liners
- Upgraded body steel package
- Body scale systems
- CNG fueling system
- Axalta Imron Elite finish paint

AUTHORIZED NEW WAY DISTRIBUTOR


^{**} Any Chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted. (Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)











^{» 9} yd³ model will be built with external hydraulic cylinders.

^{*}Approximate Body Weight empty and exclusive of options.