

# WOLVERINE™

## SERIES



## SMALL, BUT MIGHTY

The New Way® Wolverine™ is the latest innovation from New Way Trucks and joins the largest and most diverse family of refuse products in the solid waste industry. The Wolverine has all the great features of its big brother the New Way Sidewinder™, just in a smaller package.

Although the Wolverine is a full-fledged collection vehicle, it is available in an under-CDL package, making finding and training new drivers so much easier. Your new drivers can focus on safety, customer service, and a manageable route footprint in a smaller vehicle, and eventually graduate to a full-size unit bringing those skills forward to a larger yet still familiar vehicle.

The New Way Sidewinder is the best-selling Class 8 automated side loader in the industry. It's just a matter of time before the Wolverine is the best-selling Class 6.



## GENERAL SPECIFICATIONS

Model	10W	12W	14W
Body Capacity	10 yd <sup>3</sup>	12 yd <sup>3</sup>	14 yd <sup>3</sup>
Hopper Capacity	3.3 yd <sup>3</sup>	3.3 yd <sup>3</sup>	3.3 yd <sup>3</sup>
Body Width (A)	96"	96"	96"
Body Height (B)	90.5"	90.5"	90.5"
Body Length (C)	160.5"	173"	183.25"

## MINIMUM CHASSIS SPECIFICATIONS

** Minimum GVWR	26,000 lbs	26,000 lbs	27,500 lbs
-----------------	------------	------------	------------

## BODY CONSTRUCTION

Roof	12 gauge 80K
Sides	12 gauge 80K
Packer Ram	3/16" AR450
Body Floor	3/16" AR235
Tailgate	12 gauge 80K
Hopper Floor	3/16" AR235
Ram Guide	1/4" 50K formed tracks 1/4" AR450 wear strips

## HYDRAULIC SYSTEMS

Oil Reservoir	46 gal
Oil Flow Rate: Body	30 gpm @ 1,200 rpm
Oil Flow Rate: Arm	30 gpm @ 1,200 rpm
Body Pressure Relief	3,000 psi
Arm Pressure Relief	3,000 psi
Over Speed Protection	1,500 rpm
Hydraulic Tank Breather Element	10 micron
Hydraulic Hoses	4-to-1 burst
Return Line Filter	10 micron absolute
Suction Line Strainer	100 mesh

\*\*\* Minimum Cummins L9 (or equal) engine and 3,000 series transmission required.

## PACKER SPECIFICATIONS

Hopper Capacity	3.3 yd <sup>3</sup>
Packer Swept Volume	1.1 yd <sup>3</sup>
Packer Cycle Time	10-12 secs.
Min. Material Displacement Rate	4.5 yd <sup>3</sup> /min.
Packer Dimensions	13" x 70"

Body construction and packer specs subject to change as product design develops.

## ARM SPECIFICATIONS

Lifting Capacity at Max. Reach	500 lbs
Arm Cycle Time	8-10 secs.
Cart Capacity Able to Handle	36-110 gal
Arm Extension	9'
Min. Gripping Force	1,800 psi
Max. Operating Pressure	2,500 psi

\* Approximate body weight empty and exclusive of options

\*\* Any chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted. (Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)

## STANDARD EQUIPMENT

- Multi-cycle packer
- Hopper and backup cameras
- Imron elite productive paint
- High-grade hydraulic fluid
- Smooth body sidewall design
- Fully-automatic tailgate latches
- In-cab arm & tailgate controls
- Tapered body design
- Rounded & sealed tailgate
- Double-acting tailgate cylinders
- Fully-enclosed hopper sides
- Back up & license plate lights
- Back up alarm
- Arm not stowed warning light & buzzer
- ANSI Z245.1 compliant
- Body & hydraulic 1 year warranties
- LED safety lights & reflectors
- Electric proportional arm control
- Hopper rake teeth
- Partially covered hopper roof
- Hydraulic hopper cover

## OPTIONAL EQUIPMENT

- Available in fully and semi-automated configurations

AUTHORIZED NEW WAY DISTRIBUTOR



Sourcewell  
Formerly NJPPA  
Awarded Contract  
Contract # 110223-NWY

**NEW WAY®** Driving The Difference.®

a quality product of **McLaughlin** FAMILY COMPANIES • 800 831 1858 • www.newwaytrucks.com

PART NUMBER: 144699 24-3144 REV 03-24